

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A crosslinked flame-retardant resin composition comprising:  
100 part weight of a resin ingredient containing:  
  - (A) polyethylene of which a melt flow rate (MFR) is 5 g/10 min. or less and density is 0.90 g/cm<sup>3</sup> or more; and
  - (B) at least one polymer selected from:  
    - (B1) alpha-olefin (co)polymer;
    - (B2) ethylene-vinylester copolymer;
    - (B3) ethylene-alpha, beta-unsaturated carboxylic acid alkyl ester copolymer;
  - and
  - (B4) a styrene thermoplastic elastomer;  
30-250 part weight of (C) metallic hydrate; and  
1-20 part weight of (D) a zinc compound,  
wherein, in the resin ingredient, the content of (A) the polyethylene is 30-90 wt% and the content of (B) the polymer is 70-10 wt%, and  
one or both of a condition that at least one of (B) the polymer is modified by acid and a condition that 0.3-10 part weight of (E) an organo-functional coupling agent is further contained are met.
2. (Original) The crosslinked flame-retardant resin composition according to claim 1, wherein (D) the zinc compound is zinc sulfide.
3. (Currently Amended) A non-halogenous insulated wire comprising a conductor covered with the crosslinked flame-retardant resin composition according to claim 1 or 2.

4. (Original) The non-halogenous insulated wire according to claim 3, being crosslinked by one of radiation, peroxide and a silane cross-linking agent.

5. (Currently Amended) A wiring harness comprising:  
one of a single wire bundle including only the non-halogenous insulated wires according to claim 3 ~~or~~ 4, and a mixed wire bundle including at least the non-halogenous insulated wires according to claim 3 ~~or~~ 4 and vinyl chloride insulated wires; and

a wiring-harness protective material for covering the wire bundle, in which one of a non-halogenous resin composition, a vinyl chloride resin composition, and a halogenous resin composition other than the vinyl chloride resin composition is used as a base material.

6. (New) A non-halogenous insulated wire comprising a conductor covered with the crosslinked flame-retardant resin composition according to claim 2.

7. (New) The non-halogenous insulated wire according to claim 6, being crosslinked by one of radiation, peroxide and a silane cross-linking agent.

8. (New) A wiring harness comprising:  
one of a single wire bundle including only the non-halogenous insulated wires according to claim 4, and a mixed wire bundle including at least the non-halogenous insulated wires according to claim 4 and vinyl chloride insulated wires; and  
a wiring-harness protective material for covering the wire bundle, in which one of a non-halogenous resin composition, a vinyl chloride resin composition, and a halogenous resin composition other than the vinyl chloride resin composition is used as a base material.

9. (New) A wiring harness comprising:  
one of a single wire bundle including only the non-halogenous insulated wires according to claim 6, and a mixed wire bundle including at least the non-halogenous insulated wires according to claim 6 and vinyl chloride insulated wires; and

a wiring-harness protective material for covering the wire bundle, in which one of a non-halogenous resin composition, a vinyl chloride resin composition, and a halogenous resin composition other than the vinyl chloride resin composition is used as a base material.